

LOW-ENERGY PRECISION MEASUREMENTS

ELECTRON-EDM

Steven Hoekstra electron-EDM program leader Van Swinderen Institute for Particle Physics and Gravity University of Groningen

NL-eEDM

Measuring the electron-EDM with BaF molecules

Scientific staff:

Anastasia Borschevsky

Rick Bethlem

Steven Hoekstra

Klaus Jungmann

Rob Timmermans

Wim Ubachs

Lorenz Willmann

PhD students:

Parul Aggarwal Alexander Boeschoten

Kevin Esajas

Pi Haase

Yongliang Hao

Virginia Marshall

Thomas Meijknecht


Maarten Mooij

Anno Touwen

Artem Zapara

Postdocs

Malika Denis Yanning Yin



Master students:

Hidde Makaske
Sander Vermeulen
Kees Steinebach
Mark Buisman
Rutger Hof
Paul Hofland

Bachelor students:

Mairéad O'Shea Scanlan Attie Hendriks Jente Joosten Richard Borchers Marit Fiechter





university of groningen


van swinderen institute for particle physics and gravity







Is the electron round?

The Electric Dipole Moment of the electron (eEDM)




Probing new physics with the eEDM






High eEDM sensitivity by using intense beam of slow molecules



Overview



Cryogenic sources (RUG and VU)

RUG source

Goal: get quickly operational

Status:

- designed, built, operational
- SrF: velocity ~150-200 m/s
- Reached important milestone:
 - production of SrF from metal target

VU source


Goal: best BaF source possible

Status:

- Reached important milestone:
 - Two weeks ago first signal of BaF!

Guide

Goal: increase #molecules into decelerator Status: will be implemented in september





cryogenic source deceleration and guide of cryogenic Spectroscopy decelerator of BaF intensity upgrade lasercooling slow BaF calculation of molecular properties molecular laser cooling systematics and simulations **EDM** supersonic beam of BaF, measurement with fast interaction zone design BaF beam data collection, analysis

2019

Phase 2: testing and combining

People

Phase 1: construction

2017


Kevin Esajas	PhD
Maarten Mooij (VU)	PhD
Rutger Hof	Msc
Paul Hofland (VU)	Msc
Yanning Yin	Postdoc
Leo Huisman	Technican
Wim Ubachs	Staff
Steven Hoekstra	Staff
Rick Bethlem	Staff

Decelerator upgrade

High-voltage upgrade 5 -> 10 kV


Goal: 10x more molecules

Status: transformer prototype tested, bandwidth in spec: 1.5 kHz to 20 kHz



Measurement of transformer bandwidth

Phase as a function of frequency



2017 2019 202 cryogenic source deceleration and guide of cryogenic Spectroscopy decelerator of BaF intensity upgrade lasercooling slow BaF calculation of molecular properties molecular laser cooling systematics and simulations **EDM** supersonic beam of BaF, measurement with fast interaction zone design BaF beam data collection, analysis

Phase 2: testing and combining

People

Phase 1: construction


Parul Aggarwal PhD
Artem Zapara PhD
Hidde Makaske Msc
Leo Huisman Technician
Rick Bethlem Staff
Steven Hoekstra Staff

Decelerator upgrade

High-voltage upgrade 5 -> 10 kV

Goal: 10x more molecules


Status: transformer prototype tested, bandwidth in spec: 1.5 kHz to 20 kHz



Re-alignment of the decelerator

Goal: fix kink, improve module alignment **Status:**

- changed direction of decelerator
- improved alignment
- improved connections
- Reached important milestone:
 - HV conditioning complete



cryogenic source deceleration and guide of cryogenic Spectroscopy decelerator of BaF intensity upgrade lasercooling slow BaF calculation of molecular properties molecular laser cooling systematics and simulations **EDM** supersonic beam of BaF, measurement with fast interaction zone design BaF beam

2019

Phase 2: testing and combining

202

People

Phase 1: construction

2017

Parul Aggarwal
Artem Zapara
Hidde Makaske
Leo Huisman
Rick Bethlem
Staff
Steven Hoekstra
PhD
Msc
Technician
Staff

data collection,

analysis


Decelerator u

High-voltage upgrade 5 -> 10

Goal: 10x more molecules

Status: transformer prototype t bandwidth in spec: 1.5 kHz to 2





Phase 1: construction

Phase 2: testing and combining

202

lasercooling

slow BaF

EDM

measurement

7 2019

cryogenic source and guide

Spectroscopy de of BaF inten

decelerator intensity upgrade

deceleration of cryogenic BaF

calculation of molecular properties

molecular laser cooling

systematics and simulations

analysis

supersonic beam of BaF, interaction zone design

with fast
BaF beam
data collection,

People

Parul Aggarwal

Artem Zapara Hidde Makaske

Leo Huisman

Rick Bethlem

Steven Hoekstra

PhD

PhD

Msc

Technician

Staff

Staff


Calculation of molecular properties

Method development for highest accuracy

Effective electric field in BaF


Goal: interpretation of measurement


Status: most accurate value determined. Results in 2 papers, with analysis of systematic effects in calculation.



BaF molecular structure

Goal: laser cooling, state transfer Status: identified best cooling scheme, paper published in Journal of Chemical Physics





People


Pi Haase PhD
Yongliang Hao PhD
Diewertje Douglas Msc
Malika Denis Postdoc
Anastasia Borschevsky Staff

Laser systems

Goal: flexible laser system: state preparation, cooling and molecule detection

Status: laser system operational





People

Phase 1: construction


Virginia Marshall Oliver Böll Lorenz Willmann PhD Technician Staff


Phase 2: testing and combining


Supersonic beam

Goal: create a BaF beam for spectroscopy and fast-beam eEDM **Status**: supersonic beam operational

- very cold beam ~ 1K
- combined with IR excitation and fluorescence detection zone
 - spectroscopy of BaF: lifetime measurement of electronic excited state in BaF
 - paper submitted.









Interaction zone

Goal: create controlled electric (strong) and magnetic (weak) field region Status:

- design of magnetic shield, magnetic field coils and electric field plates finished
- delivery of shield, coils and plates expected. Prototype field coil manufactured @ nikhef.





Prototype field coil

cryogenic source deceleration and guide of cryogenic Spectroscopy decelerator of BaF intensity upgrade lasercooling slow BaF calculation of molecular properties molecular laser cooling systematics and simulations **EDM** supersonic beam of BaF, measurement interaction zone design with fast BaF beam data collection, analysis

2019

Phase 2: testing and combining

202

People


Phase 1: construction


2017

Thomas Meijknecht Leo Huisman Oliver Böll Lorenz Willmann Klaus Jungmann


PhD
Technician
Technician
Staff
Staff


Summary of status: phase 1 completed





Phase 2: fast beam eEDM and cold slow beam





Proud of the team!



extra material

Meeting and management structure

Meetings:

- weekly paper discussion by students
- bi-weekly friday eEDM meetings with all involved
- separate staff meetings
- yearly meeting in september: look back, plan ahead
- 2017 & 2019: International summerschool 'Search for new physics with low-energy precision tests'

Managing the program:

- decision on major investments: SH, LW, RB
- electronic logbook and document sharing




Key numbers

Table 1. The estimate of the number of molecules that can be detected per repetition of the experiment. We aim to run the experiment at 10 Hz.

Item	Number	Units	Resulting # mol./shot
Source	10^{13}	Molecules/shot	
	0.005	Extraction efficiency from buffer gas cell	
	0.24	Fraction in $v = 0, N = 2$	5×10^{10} from source; 4×10^9 in desired state,
	0.3	Fraction in low-field seeking states	$v_{long}=(180 \pm 50) \text{ m/s}, v_{trans}=\pm 30 \text{ m/s}.$
Decelerator	0.002	Fraction in velocity acceptance	
	0.3	Fraction in spatial acceptance	
	0.7	Efficiency of deceleration relative to guiding	2×10^6 , $v_{long} = (30 \pm 6)$ m/s, $v_{trans} = \pm 5$ m/s.
Laser cooling	0.8	Laser cooling efficiency	
	0.7	State transfer efficiency	9×10^5 , $v_{long} = (30 \pm 6) \text{ m/s}$, $v_{trans} = \pm 0.2 \text{ m/s}$.
Interaction zone	0.8	Transmission and state transfer efficiency	
	1.0	Detection efficiency	7×10^5

EPJD 72:197 (2018)

Key numbers



Cryogenic source data June 2019

